

Rittal – The System.

Faster – better – everywhere.



VX 8100.710

Leveling component

State: 1/18/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 8100.710 - Leveling component For VX base/plinth systems

For subsequent leveling on uneven floors at the installation site up to a maximum of 15 mm. Installed through the base/plinth corner piece.

Features

Model No.	VX 8100.710
Product description	For subsequent leveling on uneven floors at the installation site up to a maximum of 15 mm. Installed through the base/plinth corner piece. Adjust using hex wrench, width across flats 19 mm (0.74").
Benefits	A door offset caused by uneven flooring can be corrected Installed on the assembled enclosure, i.e. no need to plan leveling in advance
Supply includes	Assembly components
Load capacity	Max. permitted load: 2500 N per leveling component
Note	Can be used in combination with VX, VX IT, VX SE, TX , TS, TS IT, PC, IW or TP with VX socket system Check the load capacity of the floor.
Dimensions	Height: 100 mm Height: 3.94 "
Weight/packaging unit	0.74 kg 1.6 lb.
Packaging unit	4 pc(s).
Net weight	0.68
Gross weight	0.74
Customs tariff number	73181900
EAN	4028177921559
ETIM 9	EC000721
ECLASS 8.0	27182003