Rittal – The System.

Faster – better – everywhere.





TS 8405.500 Baying systems TS 8

State: 11/7/2025 (Source: rittal.com/us-en)



TS 8405.500 - Baying systems TS 8

Due to its symmetrical profile in terms of width and depth, the TS 8 baying system, made from carbon steel, saves considerable space and facilitates easy internal installation. It also allows a baying arrangement on all sides. In addition, the integrated, automatic potential equalization of all enclosure panels and the triple machining of the surface ensures maximum safety.

Features

Model No.	TS 8405.500
Material	Enclosure frame: Carbon steel, 1.5 mm
	Roof: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the outside, textured paint
Color	RAL 7035
Supply includes	Enclosure frame
	Door(s)
	Right-hand door catch on single-door enclosures may be swapped
	to the left
	Roof plate
	Rear panel
	4 eyebolts
	Lock: 3 mm double-bit
	Gland plate
	Mounting panel
	2 TS punched rails, 18 x 38 mm
Dimensions	Width: 400 mm
	Height: 2,000 mm
	Depth: 500 mm
	Width: 15.7 "
	Height: 78.7 "
	Depth: 19.7 "
Protection category IP to EN 60 529	IP 55

© Rittal 2025 2

Features

Protection category NEMA	NEMA 1 NEMA 12
Type rating according to UL 50E	Type 1 Type 12
IK code	IK09
Number of doors	1
Base material	Carbon steel
Packaging unit	1 pc(s).
Net weight	169.998
Gross weight	169.998
Customs tariff number	7326909099
UPC-Code	81085
ECLASS 8.0	27180101

Approvals

Approvals	Bureau Veritas UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK
	beclaration of comornity of

© Rittal 2025 3