

Rittal – The System.

Faster – better – everywhere.



TS 8601.860

Earthquake base/plinth

State: 8/29/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



TS 8601.860 - Earthquake base/plinth for VX, TS

For stable attachment of the earthquake-resistant enclosure to the subsurface External metric M6 thread for a stable connection to the subsurface from the outside.



Features

Model No.	TS 8601.860
Product description	For stable attachment of the earthquake-resistant enclosure to the subsurface. External metric M6 thread for a stable connection to the subsurface from the outside.
Material	Corner pieces: Carbon steel, 5 mm Panels: Carbon steel, 2 mm
Surface finish	Powder-coated
Color	RAL 7022
Supply includes	Base/plinth, fully assembled 4 corner pieces 2 depth stays 2 trim panels front/rear Assembly components
Note	Complies with earthquake zone 4 to Telcordia GR-63-Core in combination with the comfort handle and earthquake kit.
Dimensions	Height: 100 mm Height: 3.94 "

Features

Suitable for	Enclosure type: VX TS Width: = 800 mm Depth: = 600 mm Enclosure type: VX TS Width: = 31.5 " Depth: = 23.6 "
Packaging unit	1 pc(s).
Net weight	15.06
Gross weight	15.87
PCF/VE (cradle-to-gate)	60.6 kg CO2 eq (Cat B)
Information regarding the PCF class	Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared
Customs tariff number	94039910
EAN	4028177413597
ETIM 9	EC000721
ECLASS 8.0	27182003