Rittal – The System.

Faster - better - everywhere.





TS 8612.090 TS System Chassis 17 x 73 mm

State: 12/21/2025 (Source: rittal.com/us-en)



TS 8612.090 - TS System Chassis 17 x 73 mm

For universal skeleton structures or partial assembly. Simply locate into the punchings and secure.





Features

onto the punchings and secure. Material Carbon steel Surface finish Zinc-plated Supply includes Assembly screws Length 890 mm 35 ″ Suitable for door width 1,000 mm 39.4 ″ Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook is secure		
Product description For universal skeleton structures or partial assembly. Simply I onto the punchings and secure. Material Carbon steel Surface finish Zinc-plated Supply includes Assembly screws Length 890 mm 35 ~ Suitable for door width 1,000 mm 39.4 ~ Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook is secure	Model No.	TS 8612.090
onto the punchings and secure. Material Carbon steel Surface finish Zinc-plated Supply includes Assembly screws Length 890 mm 35 ″ Suitable for door width 1,000 mm 39.4 ″ Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Version	For mounting on doors
Surface finish Zinc-plated Supply includes Assembly screws Length 890 mm 35 " Suitable for door width 1,000 mm 39.4 " Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Product description	For universal skeleton structures or partial assembly. Simply locate onto the punchings and secure.
Supply includes Assembly screws 890 mm 35 ″ Suitable for door width 1,000 mm 39.4 ″ Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Material	Carbon steel
Length 890 mm 35 ″ Suitable for door width 1,000 mm 39.4 ″ Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Surface finish	Zinc-plated
Suitable for door width 1,000 mm 39.4 " Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Supply includes	Assembly screws
Installation options On the vertical TS, VX SE enclosure profile: on the inner moun level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Length	
level, all-round, height-offset On the horizontal VX SE enclosure section top, in depth In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Suitable for door width	·
In TP via rails for interior installation: in width, for inner mount level As installation kit for device bases in TS, VX SE, simply hook i secure	Installation options	On the vertical TS, VX SE enclosure profile: on the inner mounting level, all-round, height-offset
level As installation kit for device bases in TS, VX SE, simply hook i secure		On the horizontal VX SE enclosure section top, in depth
secure		In TP via rails for interior installation: in width, for inner mounting level
Mounting tip The rail for interior installation is required when installing in T		As installation kit for device bases in TS, VX SE, simply hook in and secure
	Mounting tip	The rail for interior installation is required when installing in TP

© Rittal 2025

Features

Suitable for	Enclosure type: VX SE
	TP
	PC
	IW
Packaging unit	4 pc(s).
Net weight	3.3
Customs tariff number	73269098
EAN	4028177232648
ETIM 9	EC002625
ECLASS 8.0	27189234

© Rittal 2025 3