Rittal – The System.

Faster – better – everywhere.



# TS 8800.520

# Cable duct

State: 11/10/2026 (Source: www.rittal.com/us-en)

# TS 8800.520 - Cable duct for vertical TS section

For mounting on a vertical enclosure profile or on two bayed enclosure profiles in the baying area.







## Features

| | |
|---|---|
| Model No. | TS 8800.520 |
| Version | Width 50 mm, for assembly on a vertical enclosure section in the side panel area. |
| Benefits | The cable duct fastening points are co-ordinated with the TS system hole pattern. This eliminates time-consuming drilling work that would be necessary with DIN ducts.<br>The nominal break points of the bars are also designed in combination with the cable ducts for mounting plates.<br>A further nominal break at the mounting plate height allows direct entry to the cable duct. |
| Material | Hard PVC<br>Flame-resistant, self-extinguishing |
| Color | Similar to RAL 7030 |
| Supply includes | Cable duct with cover |
| Bar width | 5.5 mm<br>0.22 ″ |
| Slot width | 4.5 mm<br>0.18 ″ |
| Note | Can be shortened for other enclosure sizes. |

# Features

| | |
|---|---|
| Dimensions | Width: 50 mm<br>Height: 1,800 mm<br>Depth: 80 mm<br>Width: 1.97 ″<br>Height: 70.9 ″<br>Depth: 3.15 ″ |
| Suitable for | Enclosure type: TS<br>VX SE<br>PC<br>IW<br>Height: ≤ 2,000 mm<br>Enclosure type: TS<br>VX SE<br>PC<br>IW<br>Height: ≤ 78.7 ″ |
| Operating temperature range | 60 °C<br>140 °F |
| Packaging unit | 8 pc(s). |
| Net weight | 9.944 kg |
| Gross weight | 10.52 kg |
| Customs tariff number | 39259020 |
| ETIM 9 | EC000012 |
| ECLASS 8.0 | 27400703 |
| Product description | TS Cable duct for vertical TS section, WHD:  50x1800x80 mm |

# Approvals

| | |
|---|---|
| Explanations | Declaration of conformity<br>Declaration of conformity UK |