## Rittal – The System.

Faster – better – everywhere.





# TS 8806.500 Baying systems TS 8

State: 9/4/2025 (Source: rittal.com/us-en)



## TS 8806.500 - Baying systems TS 8

Due to its symmetrical profile in terms of width and depth, the TS 8 baying system, made from carbon steel, saves considerable space and facilitates easy internal installation. It also allows a baying arrangement on all sides. In addition, the integrated, automatic potential equalization of all enclosure panels and the triple machining of the surface ensures maximum safety.



#### **Features**

Model No.	TS 8806.500
Material	Enclosure frame: Carbon steel, 1.5 mm
	Roof: Carbon steel, 1.5 mm
	Door: Carbon steel, 2.0 mm
	Rear wall: carbon steel, 1.5 mm
	Base plates: Carbon steel, 1.5 mm
	Mounting panel: Carbon steel, 3.0 mm
Surface finish	Enclosure frame: Dipcoat-primed
	Door, roof and rear panel: Dipcoat-primed, powder-coated on the
	outside, textured paint
	Mounting plate and base plates: Zinc-plated
Color	RAL 7035

© Rittal 2025 2

## Features

Enclosure frame Door(s) Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm Height: 2,000 mm
Right-hand door catch on single-door enclosures may be swapped to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
to the left Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
Roof plate Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
Rear panel 4 eyebolts Lock: 3 mm double-bit Base Plates Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
4 eyebolts  Lock: 3 mm double-bit  Base Plates  Mounting panel  2 TS punched rails, 18 x 38 mm  2 support strips fitted in the enclosure depth  Width: 800 mm
Base Plates  Mounting panel  2 TS punched rails, 18 x 38 mm  2 support strips fitted in the enclosure depth  Width: 800 mm
Mounting panel 2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
2 TS punched rails, 18 x 38 mm 2 support strips fitted in the enclosure depth Width: 800 mm
2 support strips fitted in the enclosure depth Width: 800 mm
Width: 800 mm
Height: 2,000 mm
Depth: 600 mm
Width: 31.5 "
Height: 78.7 ″ Depth: 23.6 ″
Эерин. 23.0
599 mm x 1,896 mm
27.5 ″ x 74.6 ″
P 55
NEMA 1
NEMA 12
Гуре 1
Гуре 12
K09
1
Yes
Carbon steel
1 pc(s).
123.5
128.7
94032080

© Rittal 2025 3

## Features

EAN	4028177251038
UPC-Code	38076
ETIM 9	EC000261
ECLASS 8.0	27180101

## **Approvals**

Approvals	Bureau Veritas
	Lloyds Register of Shipping
	UL + C-UL (listed)
Certificates	Surface finish
Explanations	Manufacturer's declaration
	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025