Rittal – The System.

Faster – better – everywhere.



# SV 9340.004

# Busbar Supports

State: 11/25/2026 (Source: www.rittal.com/us-en)

ENCLOSURES | POWER DISTRIBUTION | CLIMATE CONTROL | IT INFRASTRUCTURE | SOFTWARE & SERVICES

FRIEDHELM LOH GROUP

# SV 9340.004 - Busbar Supports For Flat Copper Busbars

For flat copper bars up to 800 A.

## Features

| | |
|---|---|
| Model No. | SV 9340.004 |
| Material | Polyamide<br>Fire protection corresponding to UL 94-V0 |
| Color | RAL 7035 |
| Rated operating voltage | 1000 V, 3~ |
| Note on Model No.: | When 12 x 5/10  mm busbars are used, spacer 9340.090 must also be used<br>The use of a base tray is required for UL applications.<br>UL approval only applies in conjunction with AC application |
| Electrical UL ratings (SCCR) | 22 kA - 600 V, support spacing 500 mm, busbars 15 x 5 - 25 x 10 mm<br>25 kA - 600 V, support spacing 500 mm, busbars 30 x 5/10 mm<br>30 kA - 600 V, support spacing 250 mm, busbars 15 x 5 - 25 x 10 mm<br>65 kA - 600 V, support spacing 250 mm, busbars 15 x 5 - 25 x 10 mm, fuse class L max. 800 A, JDDZ/7 |
| Number of poles | 4-pole |
| Suitable for Model No. | 3580000<br>3581000<br>3582000<br>3583000<br>3584000<br>3580100<br>3581100<br>3585005<br>3586005 |
| With internal attachment | Yes |
| Center-to-center spacing of busbars | 60 mm |

© Rittal 2026

# Features

| | |
|---|---|
| Suitable for busbars | 12 x 5 - 30 x 10 |
| Packaging unit | 4 pc(s). |
| Net weight | 0.84 kg |
| Gross weight | 0.915 kg |
| Customs tariff number | 85469010 |
| ETIM 9 | EC001166 |
| ECLASS 8.0 | 27400607 |
| Product description | SV Busbar support, 4-pole, 60 mm bar centre distance, for busbar WH: 12x5-30x10 mm, UL design |

# Approvals

| | |
|---|---|
| Approvals | ABS<br>DNV<br>Lloyds Register<br>UL + C-UL (listed) |
| Explanations | Declaration of conformity<br>Declaration of conformity UK |