Rittal - The System.

Faster – better – everywhere.





SV 9343.200 NH Fuse-Switch Disconnectors

State: 10/31/2025 (Source: rittal.com/us-en)



SV 9343.200 - NH Fuse-Switch Disconnectors

Features

Model No.	SV 9343.200
Material	Polyamide
	Fire behavior corresponding to UL 94
	Contact tracks: Electrolytic copper, silver-plated
Color	Chassis: RAL 7035
	Cover: RAL 7035/7001
Clamping area for laminated	Clamping area width: 32 mm
copper bars:	Clamping area height: 10 mm
	Clamping area width: 1.26 ″
	Clamping area height: 0.39 ″
Note	Connection of sector-shaped conductors 120 - 300 mm ²
For bar systems with center-to- center spacing	60 mm
Cable outlet	Top/bottom
Type of connection (electrical)	Box terminal
Rated operating current max.	400 A
Rated operating voltage	690 V, 3~
For NH size	2
Note	The technical data may vary in the case of UR applications. UR applications only in conjunction with "Special Purpose Fuses".
Toot on coifeation	
Test specification	IEC 60 947-3
	IEC 60 269-2 (fuse inserts)
Dimensions	Width: 210 mm
	Height: 298 mm
	Width: 8.27 "
	Height: 11.7 "
Connection of round conductors	95 - 300 mm²

© Rittal 2025

Features

Suitable for busbars	Height: 5, 10 mm Height: 0.2, 0.39 [~]
Clamping area for laminated copper bars:	20 mm 0.79 ″
Number of poles	3-pole
Packaging unit	1 pc(s).
Net weight	3.42
Gross weight	3.62
Copper weight (kg per piece)	1
Customs tariff number	85369095
EAN	4028177540385
ETIM 9	EC000249
ECLASS 8.0	27371401

Approvals

Approvals	C-UR
	CQC-CCC
	UR + C-UR (recognized)
Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3