Rittal – The System.

Faster – better – everywhere.



# RX 9360.000

# RiLineX baying set

State: 11/25/2026 (Source: www.rittal.com/us-en)

# RX 9360.000 - RiLineX baying set for board

RiLineX baying connector set for the 3-pole complete board, can be used for 550 A and 800 A. Consists of rail connector and contact hazard protection cover. For simple, drill-free baying of boards between two bayed VX enclosures.







## Features

| | |
|---|---|
| Model No. | RX 9360.000 |
| Benefits | Time saving through complete digital product data<br>Shorter mounting time thanks to pre-mounted complete board<br>Tested short circuit resistance up to max. 65 kA<br>Suitable for applications in the alternating current range up to 1,000 V AC and direct current up to 1,500 V DC<br>Tested and certified according to IEC and UL<br>Simple expansion and field alignment |
| Material | Upper part: carbon steel, zinc-plated<br>Contact plate: E-Cu, tin-plated<br>Front cover: polyamide (PA 6)<br>Fire behavior corresponding to UL 94 |
| Color | RAL 35745 |
| Supply includes | 3 rail connectors<br>1 front cover<br>1 insulating plate |
| Protection category IP to IEC 60 529 | IP 2XB |

© Rittal 2026

# Features

| | |
|---|---|
| Standards | IEC 61 439-1/-2<br>UL 508 |
| Rated current max. | 780 A |
| Rated current (UL) | 780 A |
| Electrical UL ratings (SCCR) | 52.5 kA - 600 V, RMS, unprotected<br>100 kA - 600 V, fuse class L max. 1600 A, JDDZ/7<br>100 kA - 600 V, circuit breaker max. 600 A, DIVQ/7<br>100 kA - 480 V, circuit breaker max. 800 A, DIVQ/7<br>65 kA - 600 V, circuit breaker max. 800 A, DIVQ/7 |
| Rated impulse withstand voltage UImp | 12 kV |
| Rated voltage | 1,000 V AC<br>1,500 V DC<br>600 V AC (UL)<br>600 V DC (UL) |
| Rated insulation voltage Ui | 1,000 V AC<br>1,500 V DC |
| Rated impulse withstand current | 103 kA<br>115.5 kA |
| Rated short-time withstand current/t | 45 kA/200 ms<br>52.5 kA/500 ms |
| Overvoltage category | 4 |
| Contamination level | 3 |
| Number of poles | 3-pole |
| Suitable for Model No. | 9360004<br>9360008<br>9360024<br>9360028<br>9360064<br>9360068<br>9360084<br>9360088 |
| Fundamental frequency | 50...60 Hz |

© Rittal 2026

# Features

| | |
|---|---|
| Ambient humidity (non-condensing) | 10...90 % |
| Suitable for busbars | 30 x 5/10 |
| Operating temperature range | -5 °C...55 °C<br>23 °F...131 °F |
| Dimensions | Width: 154 mm<br>Height: 240 mm<br>Depth: 77 mm<br>Width: 6.06 ″<br>Height: 9.45 ″<br>Depth: 3.03 ″ |
| Fire load | 5.933 MJ/m² |
| Packaging unit | 1 pc(s). |
| Net weight | 1.88 kg |
| Gross weight | 1.924 kg |
| Copper weight (kg per piece) | 0.297 |
| PCF/VE (cradle-to-gate) | 10.32 |
| Customs tariff number | 85369010 |
| ETIM 9 | EC002270 |
| Product description | RX baying set incl. connector for RiLineX Board 3-pole |

# Approvals

| | |
|---|---|
| Approvals | UL + C-UL (listed) |
| Explanations | Declaration of conformity<br>PCF-declaration |