


Rittal – The System.

Faster – better – everywhere.



RX 9360.705

RiLineX device carrier

State: 2/17/2026 (Source: ittal.com/us-en)



FRIEDHELM LOH GROUP

RX 9360.705 - RiLineX device carrier without contact system

Component support without contact system 45 mm.



Features

Model No.	RX 9360.705
Version	without contact system
Benefits	For mounting equipment for top-hat rail mounting, e.g. motor starter Simple connector lock for component support rails Optional component anti-slip guard Reduction of article variety through coordinated accessories Snap-on mounting and easy adjustment on busbar thickness 5/10 mm
Material	Polyamide (PA 6) Fire behavior corresponding to UL 94
Color	RAL 9005
For bar systems with center-to-center spacing	60 mm
Dimensions	Width: 45 mm Height: 239.4 mm Depth: 36.2 mm Width: 1.77 " Height: 9.43 " Depth: 1.43 "

Features

Suitable for busbars	15 x 5/10 20 x 5/10 30 x 5/10
Suitable for busbar system	RiLineX RiLine60
Number of poles	3-pole
Support rails Qty	1
Rated voltage	690 V AC 600 V AC (UL) 600 V DC (UL)
Packaging unit	4 pc(s).
Net weight	1.16
Gross weight	1.2
Customs tariff number	85369095
EAN	4028177997059
ETIM 9	EC001531

Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity
