

# Rittal – The System.

Faster – better – everywhere.



## RX 9360.705 RiLineX device carrier

State: 6/6/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE



SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# RX 9360.705 - RiLineX device carrier without contact system

RiLineX device carrier with a width of 45 mm for RiLineX and 60 mm busbar system platforms, without contact system. Ideal if wider devices are to be affixed to the board.



## Features

Model No.	RX 9360.705
Version	without contact system
Benefits	For mounting equipment for top-hat rail mounting, e.g. motor starter Simple connector lock for component support rails Optional component anti-slip guard Reduction of article variety through coordinated accessories Snap-on mounting and easy adjustment on busbar thickness 5/10 mm
Material	Polyamide (PA 6) Fire behavior corresponding to UL 94
Color	RAL 9005
For bar systems with center-to-center spacing	60 mm

# Features

Dimensions	Width: 45 mm Height: 239.4 mm Depth: 36.2 mm Width: 1.77 " Height: 9.43 " Depth: 1.43 "
Suitable for busbars	15 x 5/10 20 x 5/10 30 x 5/10
Suitable for busbar system	RiLineX RiLine60
Number of poles	3-pole
Support rails Qty	1
Rated voltage	690 V AC 600 V AC (UL) 600 V DC (UL)
Packaging unit	4 pc(s).
Net weight	1.16 kg
Gross weight	1.2 kg
PCF/VE (cradle-to-gate)	7.39
Customs tariff number	85369095
ETIM 9	EC001531
Product description	RX component support W: 45 mm, without contact system

# Approvals

Approvals	UL + C-UL (listed)
Explanations	Declaration of conformity PCF-declaration