Rittal – The System.

Faster – better – everywhere.





PK 9500.000 PK Polycarbonate Housings

State: 12/3/2025 (Source: rittal.com/us-en)



PK 9500.000 - PK Polycarbonate Housings without knockouts

Wall-mounted enclosure of fiberglass-reinforced polycarbonate. Protection category IP 66. Covers feature quick-release fasteners for speedy maintenance. Self-extinguishing material for safety.







Features

PK 9500.000
PK housing with closed cover
Use in ambient temperature range: -35°C+80°C. The specified temperatures can be limited by the installed equipment.
Housing: Fiber-glass reinforced polycarbonate Cover gray: Fiberglass-reinforced polycarbonate, all-round foamed PU seal Cover screws: Polyamide Insulating bungs: Polythene
RAL 7035
Housing with cover Cover screws Insulating bungs for wall mounting screws
NEMA 4X
IP 66

© Rittal 2025

Features

IK code	IK08
Dimensions	Width: 65 mm
	Height: 65 mm
	Depth: 57 mm
	Width: 2.56 "
	Height: 2.56 ″
	Depth: 2.24 "
Operating temperature range	-35 °C80 °C
	-31 °F176 °F
Base material	Polycarbonate
Packaging unit	12 pc(s).
Net weight	1.092
Gross weight	1.295
Customs tariff number	94037000
EAN	4028177138933
ETIM 9	EC000261
ECLASS 8.0	27180101

Approvals

Approvals	C-UL
	DNV-GL
	UL
	UL + C-UL (listed)
Explanations	Declaration of conformity

© Rittal 2025 3