Rittal – The System.

Faster – better – everywhere.





SV 9670.025 Baying systems TS 8

State: 12/8/2025 (Source: rittal.com/us-en)



SV 9670.025 - Baying systems TS 8 Isolator enclosure

TS 8 baying system for the distribution of electrical power with switch disconnector fuses from Jean Müller or ABB.

Features

| Carbon steel Enclosure frame: Dipcoat-primed Door(s), roof, rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated RAL 7035 |
|--|
| Enclosure frame: Dipcoat-primed Door(s), roof, rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated |
| Door(s), roof, rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated |
| outside, textured paint Base plates: Zinc-plated |
| Base plates: Zinc-plated |
| |
| RAL 7035 |
| |
| Enclosure frame with r/h door hinge, left side open |
| Roof |
| Rear panel |
| Base plates, three-piece |
| Lock: 3 mm double-bit |
| 4 eyebolts |
| Locating frame for isolators with fuses (brands ABB SlimLine/Jean |
| Müller SASIL) |
| IEC 61 439-1/-2 |
| IEC 61 641 |
| Up to IP 3X, depending on the panels |
| Width: 1,000 mm |
| Height: 2,200 mm |
| Depth: 600 mm |
| Width: 39.4 " |
| Height: 86.6 " |
| Depth: 23.6 " |
| 1 pc(s). |
| 133.5 |
| 144.2 |
| |

© Rittal 2025

Features

| EAN | 4028177814554 |
|------------|---------------|
| ETIM 9 | EC002525 |
| ECLASS 8.0 | 27180101 |

Approvals

| Explanations | Declaration of conformity |
|--------------|------------------------------|
| | Declaration of conformity UK |

© Rittal 2025 3