

Rittal – The System.

Faster – better – everywhere.



SV 9676.007 Spacer

State: 8/3/2025 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



SV 9676.007 - Spacer

When using smaller busbar widths, the spacer should be inserted into the chambers of the support to compensate for width differences.

Features

Model No.	SV 9676.007
Position of the bar system in the functional space	2 1 2
Note	At a bar width < 60 mm for Flat-PLS 60 or < 100 mm for Flat-PLS 100, the spacer should be used.
Suitable for busbar system	Flat-PLS 60 Flat-PLS 100
Suitable for busbars	Flat copper busbars Flat copper busbars Flat copper busbars
Suitable for busbars	Width: 40, 50, 80 Height: 10, 10, 10 mm Width: 1.57, 1.97, 3.15 Height: 0.39, 0.39, 0.39 ~
Packaging unit	16 pc(s).
Net weight	0.064
Gross weight	0.081
Customs tariff number	73269098
EAN	4028177599437
ETIM 9	EC001900
ECLASS 8.0	27400613

Approvals

Approvals

ABS

DNV-GL

Lloyds Register of Shipping