Rittal – The System.

Faster – better – everywhere.





SV 9676.520 Contact maker

State: 7/31/2025 (Source: rittal.com/us-en)



SV 9676.520 - Contact maker for connection brackets

To connect connection brackets and connector kits with flat copper bars to Flat-PLS busbar systems, no drilling required.

Features

Model No.	SV 9676.520
Product description	For joining connection brackets to busbar systems.
Material	E-Cu
Supply includes	Assembly components
For Busbar width	100 mm
Number of bars per conductor	2
Note	The screws included with the supply are used to secure the contacts to the busbars Screws for fixing the connecting bracket are not included with the supply The required screw length must be selected according to the busbar width W, i.e., Length = W + fastening measurement + (number of partial conductors x 10) Number of screws per bracket: With 2 subconductors per conductor: 2 pc(s) and with 3 or 4 subconductors per conductor 4 pc(s).
Suitable for busbar system	Flat-PLS
Mounting dimensions	40 mm 1.57 ″
Packaging unit	1 pc(s).
Net weight	0.839
Gross weight	0.868
Copper weight (kg per piece)	0.72
Customs tariff number	74198090
EAN	4028177602731

© Rittal 2025

Features

ETIM 9	EC001900
ECLASS 8.0	27400613

Approvals

Explanations	Declaration of conformity
	Declaration of conformity UK

© Rittal 2025 3