


# Rittal – The System.

Faster – better – everywhere.



## SV 9676.546 Contact maker

State: 6/8/2026 (Source: [rittal.com/us-en](http://rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



# SV 9676.546 - Contact maker for connection brackets

To connect connection brackets and connector kits with flat copper bars to Flat-PLS busbar systems, no drilling required.



## Features

Model No.	SV 9676.546
Product description	For joining connection brackets to busbar systems.
Material	E-Cu
Supply includes	Assembly components
For Busbar width	60 mm
Rails per conductor	3 4
Note	<p>The screws included with the supply are used to secure the contacts to the busbars</p> <p>Screws for fixing the connecting bracket are not included with the supply</p> <p>The required screw length must be selected according to the busbar width W, i.e., <math>\text{Length} = W + \text{fastening measurement} + (\text{number of partial conductors} \times 10)</math></p> <p>Number of screws per bracket: With 2 subconductors per conductor: 2 pc(s) and with 3 or 4 subconductors per conductor 4 pc(s).</p>
Suitable for busbar system	Flat-PLS
Mounting dimensions	40 mm 1.57 "
Packaging unit	1 pc(s).

# Features

---

Net weight	1.15 kg
Gross weight	1.254 kg
Copper weight (kg per piece)	0.93
Customs tariff number	74198090
ETIM 9	EC001900
ECLASS 8.0	27400613
Product description	SV Contact maker E-Cu, WH: 60x20 mm, for 3 or 4 strands, (Flat-PLS)

# Approvals

---

Explanations	Declaration of conformity Declaration of conformity UK
--------------	---