


Faster – better – everywhere.





## VX 9680.606 Baying-enclosure system VX25

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 6/24/2025 (Source: rittal.com/us-en)

POWER DISTRIBUTION >> CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

# VX 9680.606 - Baying-enclosure system VX25 Modular enclosure

VX baying system for installation with partial doors and inner compartmentalization in a modular design.

#### Features

Model No.	VX 9680.606
Material	Carbon steel, 1.5 mm
Surface finish	Enclosure frame: Dipcoat-primed Rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated
Color	RAL 7035
Supply includes	Enclosure frame Rear panel Base Plates
Protection category IP to EN 60 529	Up to IP 54, depending on the panels
Test specification	IEC 61 439-1/-2 IEC 61 641
Dimensions	Width: 600 mm Height: 2,000 mm Depth: 600 mm Width: 23.6 " Height: 78.7 " Depth: 23.6 "
Packaging unit	1 pc(s).
Net weight	41.82
Gross weight	45.2
PCF per pack (cradle-to-gate)	125.7 kg CO2 eq (Cat B)

#### Features

Note on PCF category	Category B: PCF value (cradle-to-gate) based on the product weight, approximately calculated and self-declared
EAN	4028177929579
ETIM 9	EC000261
ECLASS 8.0	27180101

### Approvals

Surface finish
Declaration of conformity
Declaration of conformity UK