

Rittal – The System.

Faster – better – everywhere.



VX 9680.826 Modular enclosure

State: 7/2/2026 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



VX 9680.826 - Modular enclosure Baying-enclosure system VX25

VX baying system for installation with partial doors and inner compartmentalization in a modular design.

Features

| | |
|------------------------------------|---|
| Model No. | VX 9680.826 |
| Material | Carbon steel, 1.5 mm |
| Surface finish | Enclosure frame: Dipcoat-primed Rear panel: Dipcoat-primed, powder-coated on the outside, textured paint Base plates: Zinc-plated |
| Color | RAL 7035 |
| Supply includes | Enclosure frame Rear panel Base Plates |
| Protection category IP to EN 60529 | Up to IP 54, depending on the panels |
| Test specification | IEC 61 439-1/-2 IEC 61 641 |
| Dimensions | Width: 800 mm Height: 2,200 mm Depth: 600 mm Width: 31.5 " Height: 86.6 " Depth: 23.6 " |
| Packaging unit | 1 pc(s). |
| Net weight | 53.25 kg |
| Gross weight | 58.2 kg |
| PCF/VE (cradle-to-gate) | 146.3 kg CO2 eq (Cat B) |

Features

| | |
|-------------------------------------|--|
| Information regarding the PCF class | Category B: PCF value (cradle-to-gate) calculated approximately on the basis of the product weight and self-declared |
| Customs tariff number | 94032080 |
| ETIM 9 | EC000261 |
| ECLASS 8.0 | 27180101 |
| Product description | VX Modular enclosure, WHdepth 800x2200x600 mm, sheet steel |

Approvals

| | |
|--------------|----------------|
| Certificates | Surface finish |
|--------------|----------------|