Rittal – The System.

Faster – better – everywhere.





CS 9781.888 CS Toptec, bayable

State: 10/27/2025 (Source: rittal.com/us-en)



CS 9781.888 - CS Toptec, bayable

Bayable, double-walled outdoor housing with 100 mm base, door, rear panel, and seamlessly bayable weatherproof roof. The complete enclosure frame is available for efficient and flexible interior fitting.







Features

Model No.	CS 9781.888
Version	For baying
	Without cut-out
Material	Housing frame: Stainless steel 1.4301 (AISI 304)
	Enclosure panels and base/plinth panels: Aluminum, AlMg3
	Rain canopy: Aluminum
Surface finish	Powder-coated
	UV-resistant pure polyester
Color	RAL 7035
Supply includes	Bayable, double-walled outdoor housing
	Enclosure frame with 25 mm system perforation in roof and base
	frames as well as vertical profiles with 2 mounting levels
	Front door with door stay, swing lever handle and semi-cylinder, lock
	BJ20027
	Rear panel
	Rain canopy
	Base/plinth with screw-fastened flange plates and screw-fastened
	trim panels front and rear
	Door hinged on the right, may be swapped to the left

© Rittal 2025

Features

Dimensions	Width: 800 mm Height: 1,800 mm
	Depth: 800 mm
	Width: 31.5 "
	Height: 70.9 "
	Depth: 31.5 "
Dimensions	Overall height: 1,945 mm
	Rain canopy height: 45 mm
	Height of base/plinth: 100 mm
	Rain canopy height: 1.77 ″
	Height of base/plinth: 3.94 ″
Number of doors	1
Lock	Lock version: 4-point locking system
	No. of locks: 1
	Lock Insert: BJ20027
Gland plate	Size: 2
	Qty.: 2
Protection category IP to IEC 60 529	IP 55
Protection category NEMA	NEMA 3R
	NEMA 12
IK code	IK10
Note	All enclosure panels are double wall and grounded (external wall to internal wall)
	For the assembly of an enclosure, side panels for CS Toptec, bayable are required
Packaging unit	1 pc(s).
Net weight	81.5
Gross weight	91.5
EAN	4028177986220
ETIM 9	EC000261
ETIM 8	EC000261
ECLASS 8.0	27180101

© Rittal 2025 3

Approvals

Explanations

Declaration of conformity

© Rittal 2025