Rittal – The System.

Faster – better – everywhere.





CS 9784.540 Outdoor Basic enclosure

State: 5/15/2024 (Source: rittal.com/us-en)



CS 9784.540 - Outdoor Basic enclosure

Single-walled housing systems, one-door and two-door. Ready for use for all applications with passive interior equipment or low power dissipation in outdoor areas. Roof concept with all-round louvred grilles

Features

Model No.	CS 9784.540
Version	Enclosure with width 1200 mm has two 600 mm-wide mounting panels
Product description	Outdoor housing with 100 mm transport base/plinth and rain canopy projecting on all sides.
Material	Aluminum AlMg3
Surface finish	Powder-coated UV-resistant pure polyester
Color	RAL 7035
Supply includes	Single-walled outdoor enclosure, fully preconfigured Basic enclosure with gland plate, three-part 25 mm system punchings in the roof, base, front and in the enclosure depth Front door(s) with door stay, swing lever handle and semi-cylinder lock BJ20027 Transport plinth with screw-fastened trim panels front and rear Rain canopy
Dimensions	Width: 1,200 mm Height: 1,200 mm Depth: 500 mm Width: 47.2 " Height: 47.2 " Depth: 19.7 "

© Rittal 2024 2

Features

Dimensions	Overall height: 1,355 mm
	Rain canopy width: 1,250 mm
	Rain canopy height: 55 mm
	Rain canopy depth: 550 mm
	Clearance width: 1,112 mm
	Clearance height: 1,112 mm
	Clearance depth: 449 mm
	Height of base/plinth: 100 mm
	Rain canopy width: 49.2 ″
	Rain canopy height: 2.17 ″
	Rain canopy depth: 21.7 ″
	Clearance width: 43.8 ″
	Clearance height: 43.8 "
	Clearance depth: 17.7 "
	Height of base/plinth: 3.94 ″
Design Centre bar	With removable centre bar, 2 lockable doors
Number of doors	2
Protection category IP to IEC 60 529	IP 55
Protection category NEMA	NEMA 3R
IK code	IK10
Base material	Aluminum
Packaging unit	1 pc(s).
Weight/packaging unit	66 kg
	145.5 lb.
EAN	4028177569218
ETIM 7.0	EC000261
ECLASS 8.0	27180101

Approvals

Explanation of comorning	Explanations	Declaration of conformity
--------------------------	--------------	---------------------------

© Rittal 2024 3