## Rittal – The System.

Faster – better – everywhere.





# CS 9791.045 Outdoor Wall-mounted enclosure

IT INFRASTRUCTURE SOFTWARE & SERVICES

State: 7/14/2025 (Source: rittal.com/us-en)

POWER DISTRIBUTION >> CLIMATE CONTROL



FRIEDHELM LOH GROUP

ENCLOSURES

### CS 9791.045 - Outdoor Wall-mounted enclosure

Outdoor housings for wall or pole mounting. Enclosure-within-an-enclosure concept, outer enclosure with cut-out at the bottom and integrated louvers on the rear and side panels for ventilation.



#### Features

Model No.	CS 9791.045
Product description	Outdoor housings for wall or pole mounting. Housing-within-a- housing concept, outer enclosure with cut-out at the bottom and integrated louvers on the rear and side panels for ventilation
Material	Enclosure and mounting plate: Aluminum AlMg3 Door inner casing: Stainless steel 1.4301 (AISI 304)
Surface finish	Housing: powder-coated, UV-resistant pure polyester
Color	RAL 7035
Supply includes	Double-walled outdoor housing, fully preconfigured Inner enclosure with mounting plate, gland plate and security lock Mounting bracket for enclosure internal thermostat or hygrostat Outer housing with designer cover and security lock 3524 E 2 C rails on the rear panel 2 security locks

### Features

Width: 630 mm Height: 780 mm Depth: 380 mm Width: 24.8 <sup>"</sup> Height: 30.7 <sup>"</sup> Depth: 15 <sup>"</sup>
Clearance width: 560 mm Clearance height: 560 mm Clearance depth: 308 mm Clearance width: 22 ″ Clearance height: 22 ″ Clearance depth: 12.1 ″
550 mm x 550 mm 21.7 ″ x 21.7 ″
Width: 580 mm Height: 580 mm Depth: 333 mm Width: 22.8 ″ Height: 22.8 ″ Depth: 13.1 ″
Lock version: Cam No. of locks: 2
IP 55
Delivery times on request.
Aluminum
1 pc(s).
22.254
23.425
94032080
4028177193727
EC000261
27180101



Explanations

Declaration of conformity Declaration of conformity UK