

Rittal – The System.

Faster – better – everywhere.



CS 9888.560

CS Toptec

State: 1/19/2026 (Source: [rittal.com/us-en](https://www.rittal.com/us-en))

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



CS 9888.560 - CS Toptec

Outdoor enclosure with 100 mm transport base/plinth and rain canopy with projections on all sides. Side panels, rear panel and door fully double-walled on the outside, the entire TS8 frame is available for interior installation.



Features

| | |
|---------------------|--|
| Model No. | CS 9888.560 |
| Version | With cut-out for outdoor climate control unit 6824.28 - 17060.71 BTU/h |
| Product description | Outdoor enclosure with 100 mm transport base/plinth and rain canopy with projections on all sides. Side panels, rear panel and door fully double-walled on the outside, the entire TS8 frame is available for interior installation. |
| Material | Housing frame: Stainless steel 1.4301 (AISI 304) Enclosure panels and base/plinth panels: Aluminum, AlMg3 Rain canopy: Aluminum |
| Surface finish | Powder-coated UV-resistant pure polyester |
| Color | RAL 7035 |

Features

| | |
|-------------------------------------|---|
| Supply includes | <p>Double-walled outdoor housing, fully preconfigured</p> <p>Enclosure frame with 25 mm system perforation in roof and base frames as well as vertical profiles with 2 mounting levels</p> <p>Front door with door stay, swing lever handle and semi-cylinder, lock BJ20027</p> <p>Side panels left and right</p> <p>Rear panel</p> <p>Rain canopy</p> <p>Base/plinth with screw-fastened flange plates and screw-fastened trim panels front and rear</p> |
| Dimensions | <p>Width: 800 mm</p> <p>Height: 1,800 mm</p> <p>Depth: 800 mm</p> <p>Width: 31.5 "</p> <p>Height: 70.9 "</p> <p>Depth: 31.5 "</p> |
| Protection category IP to IEC 60529 | IP 55 |
| Protection category NEMA | <p>NEMA 3R</p> <p>NEMA 12</p> |
| IK code | IK10 |
| Note | <p>All enclosure panels are double wall and grounded (external wall to internal wall)</p> <p>CS Toptec is the foundation for project solutions in the outdoor sector. It can be requested under these order numbers: For individual installations: 9774.099, for buying: 9774.005</p> |
| Note on Model No.: | A climate control unit is needed to seal the cut-out |
| Base material | Aluminum |
| Packaging unit | 1 pc(s). |
| Net weight | 116 |
| Gross weight | 118 |
| EAN | 4028177981942 |
| ETIM 9 | EC000261 |
| ECLASS 8.0 | 27180101 |

Approvals

Explanations

Declaration of conformity