

Rittal – The System.

Faster – better – everywhere.

Aisle containment – SK 3311.280

Date : 20.9.2020

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE

SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



Aisle containment – SK 3311.280

created: 20.09.2020 build on www.rittal.com/si-sl



Product description

Design:	Roof element start/end
Description:	Slimline door element with viewing window and sliding door. Stable roof elements in a composite material with a high level of light permeability. Where required, safety glass may also be used. The aisle width is 1,200 mm.
Benefits:	Increased energy efficiency and performance capability of climate control Easily installed and retrofitted, as it is fully compatible with the VX IT rack system An inexpensive way to boost the performance of your existing installation, lengthening the investment cycle until a replacement needs to be purchased
Applications:	Depending on the application, aisle containment may be used with CRAC systems or LCP Inline as hot or cold aisle containment
Function principle:	Aisle containment is a combination of door and roof components which facilitate consistent separation of the hot and cold air in the data centre. Such separation is pivotal to saving energy and increasing the efficiency of the available climate control technology.
Material:	Sheet steel, spray-finished
Colour:	RAL 7035

Product features

Dimensions:	Width: 800 mm Depth: 1200 mm
eCl@ss 8.0/8.1:	27182102

Packs of:	1 pc(s).
Weight/pack:	28 kg
EAN:	4028177716995
Customs tariff number:	73269098
ETIM 7.0:	EC002525
ETIM 6.0:	EC002525
eCl@ss 8.0/8.1:	27182102
eCl@ss 6.0/6.1:	27182102
Product description:	SK Aisle containment, Roof element, start/end, WxD: 800x1200 mm, RAL 7035
Approvals	
Certificates:	EAC